

**ACRYLIC PAINT – GLOSSY ACRYLIC FINAL COATING (ACRO 215)****Product description:**

This coating is based on acrylic emulsion polymer with excellent resistance to washing and different atmospheric conditions, it is a very suitable substitute for oil paints, which has excellent flexibility and durability, and at the same time has the characteristic of quick drying, ease of implementation and excellent coverage with surface creation. Completely uniform and beautiful, it can create a pleasant environment.

Application:

This product is for painting plaster, cement and concrete surfaces, etc. inside and outside the building.

Technical data:

Specification	Details	EN Standard	ASTM Standard
Appearance	Glossy	EN ISO 7724	D2244
Glossy (under angle 85)	Max 60	EN ISO 13300	D523
Shades(color)	White and colorful	EN ISO 7724	D2244
Solid by weight %	2.1 - 3.1 g/cm ³	EN ISO 3251	D2369
Solid by volume %	110 ±.5	EN ISO 3233	D2697
Density g/cm ³	1.4 - 1.6 g/cm ³	EN ISO 2811	D1475
Hardening mechanism:	Evaporation of water	-	-
Viscosity	80 - 135 Krebs	EN ISO 2431	D1200
Theoretical coverage	6 - 8 m ² /l	EN ISO 6504-1	D344
Surface Drying	Max 1 hours	EN ISO 9117	D1640
Through Dry(Dep Dry)	Max 3 hours	EN ISO 9117-1	D1640

Surface Preparation:

The desired surface should be clean, dry and free from any contamination. New plaster surfaces usually do not need to be prepared, but old surfaces must be primed.

Method of Applying:

- Putty the surface if needed.
- Mix the plastic color with the right amount of water and apply it on the surface.

Equipment Used: Spray, brush, roller**Safety Tips:**

This product is water-based and not flammable. However, it is recommended that in case of contact with the skin, wash it with soap and large amounts of water, and in case of further skin sensitivity and irritation, see a doctor.

Storage Conditions:

This product should be in a closed space and away from direct rays .The temperature should be kept at 5 - 35 degrees Celsius.

packing:

Gallon (Plastic can)

2.5 Gall (Plastic can)

Considerations:

The available information is based on our technical conditions and methods of application are different and out of reach, we do not guarantee the results of it.

Environmental Conditions:

This product can be run at 10 - 35°C on dry place.



LEGAL NOTES : The information contained in this Technical Data Sheet is based on laboratory testing and practical experience. Actual performance may vary depending on substrate condition, application method, and environmental conditions. Users should test suitability before large-scale application.

Head Office : Building No.15 , Qasimlu Street 40, Shahidan Zargata Quarter 24, Zone 1, Sulaymaniyah 46001, Iraq

Factory : Tanjaro Industrial Area – Sulaymaniyah – Iraq