



Product description:

This coating is based on emulsion acrylic polymer and resistant pigments with excellent resistance to washing and weather conditions, it is a very suitable substitute for oil paints, and it has excellent flexibility and durability, and it also has the characteristics of quick drying and ease of application with excellent coverage. And a completely uniform and beautiful surface can create a pleasant environment.

Application:

This product can be used for painting the interior surfaces of the building on plaster, cement and concrete surfaces, etc.

Technical data:

Specification	Details	EN Standard	ASTM Standard
Appearance	semi-opaque	EN ISO 7724	D2244
Shades(color)	White and colorful	EN ISO 7724	D2244
Density g/cm ³	0.05 - 1.4 g/cm ³	EN ISO 2811	D1475
Viscosity	5 ± 115 Krebs	EN ISO 2431	D1200
Theoretical Spreading Rate (m ² /L)	8 - 10 m ² / liter	EN ISO 6504-1	D344
Surface Drying	15 - 20 Min	EN ISO 9117	D1640
Through Dry(Dep Dry)	Max 2 hours	EN ISO 9117-1	D1640

Environmental Conditions:

This product can be run at 5 - 35°C on dry place.



ACRYLIC PAINT – LUSHIN VELVET ACRYLIC PAINT (ACRO • 211)

Surface Preparation:

The surface must be clean, dry and free from any contamination. If there are old colors, sand the surface and then apply the color.

Method of Applying:

- Putty the surface if needed.
- Dilute Primer 100 with some water on surfaces that have not been painted before or have pores and apply on the surface.
- Stir the paint completely and dilute with water to the required amount, then apply.

Equipment Used: Brush, roller, spray

Safety Tips: This product is water-based and not flammable. However, it is recommended that in case of contact with the skin, wash it with soap and large amounts of water, and in case of further skin sensitivity and irritation, see a doctor.

Storage Conditions:

This product should be in a closed space and away from direct rays .The temperature should be kept at 5 - 35 degrees Celsius.

packing:

Gallon (Plastic can)

2.5 Gall (Plastic can)

Considerations:

The available information is based on our technical knowledge and laboratory research, but since the conditions and methods of application are different and out of reach, we do not guarantee the results of it.

LEGAL NOTES : : The information contained in this Technical Data Sheet is based on laboratory testing and practical experience. Actual performance may vary depending on substrate condition, application method, and environmental conditions. Users should test suitability before large-scale application.

Head Office : Building No.15 , Qasimlu Street 40, Shahidan Zargata Quarter 24, Zone 1, Sulaymaniyah 46001, Iraq

Factory : Tanjaro Industrial Area – Sulaymaniyah – Iraq